

#### Dorland Industrial Intrinsically Safe 5G Smartphone Extreme\_5G

Developed by Beijing Dorland System Control Technology Co. Ltd., the industrial Intrinsically Safe 5G Smartphone Extreme\_5G adopts advanced technology with intrinsically safe circuit, 6.39" 19.5:9 touch screen and 16M (Front Camera) &48M+8M+2M+30W (Rear Camera). Its waterproof and dustproof performance can meet the international IP68 standards. Side fingerprint unlock function, NFC function meets read-write needs on any occasion. In addition, built-in GPS+Beidou+Galileo+Glonass and other functions are suitable for outdoor construction and pipeline inspection. ExTreme\_5G can also cooperate with OA office system, checking positioning system and data acquisition system etc. This model is especially suitably used in dangerous environment such as petroleum, chemical, pharmaceutical, oil depot, tank farm as well as the dangerous sites with combustible and explosive gas. It is convenient for users' timely production dispatching and communication.

IP Grade: IP68

Ex-mark: Ex ib IIC T4 Gb / Ex ibD 21 T130°C

Certificate no.: CCRI 21.2841

OS: Android 11.0

Screen: 6.39 inches, 19:9 720\*1560 HD+

Memory: 8GB+128GB

Platform: MTK6833 天玑 700 8core

Camera: 48+8+2+0.3 MP (REAR) 16MP (FRONT)

Battery: 8500mAh 4.4V

Frequency: GSM: B2/3/5/8 WCDMA: B1/2/4/5/6/8/19

CDMA:BC0/BC1/BC10

LTE\_FDD(B1/2/3/4/5/7/8/12/13/17/18/19/20/25/26/28A/28B/66)

LTE\_TDD(B34/38/39/40/41)

NR(N1/3/5/7/8/20/28/38/40/41/77/78/79)

Size: 169.3\*81.2\*16.1mm

WIFI: Support, 2.4G/5G (802.11ac/a/b/g/n)

USB interface: Type C



DORLAND www.dorland-tech.com

Sensor: G-sensor, Proximity sensor, Ambient light senor, Compass (magnetic), Geomagnetism, Gyroscope

GPS: Support, Beidou, Galileo, Glonass, GPS

Bluetooth: 5.2 Side fingerprint identification: Support







Certifi	cate parameters	Description
Certificate parameters	Ex-mark	Ex ib IIC T4 Gb / Ex ibD 21 T130℃
	Certification No.	CCRI 21.2841
	IP Grade	IP68
Pro	duct overview	Description
	Unit weight	340g (including battery)
Product	Dimensions (mm)	169.3*81.2*16.1mm
overview	Operating system	Android 11.0
Hardw	are configuration	Description
	Model	MT6833 天玑 700
	Feature	8 core
CPU		2*2.2GHZ A76
	Framework	6*2.0GHZ A55
	Technology	7nm
ODLI	ODLI del	ARM Mali-Natt MC2
GPU	GPU model	Manhattan 3.0 40fps
Vi-la a	Video encode	MPEG4/H.263/264/HEVC/HEIF
Video	Video decode	(2K)2560*1440 30fps, HEVC/H.264//VP9/DVIX/MPEG4/HEIF
	Network	GSM/WCDMA/CDMA/LTE_FDD/LTE_TDD/NR
	Frequency	GSM: B2/3/5/8 WCDMA: B1/2/4/5/6/8/19 CDMA:BC0/BC1/BC10
Network		LTE_FDD(B1/2/3/4/5/7/8/12/13/17/18/19/20/25/26/28A/28B/66)
		LTE_TDD(B34/38/39/40/41) NR(N1/3/5/7/8/20/28/38/40/41/77/78/79)
	EDGE/GPRS	Support
	RAM	8GB /DDR4
Storage	ROM	128GB /DDR4
	SIM card type	Support, Nano SIM+Nano SIM
	Front Camera 16MP	
	Sensor	SONY IMX351-OAPHS-C 1600W
Front	Sensing area	1/3inch
Camera	Pixel area	4688*3512
Camera	Aperture	F/2.0±5%
	Sensor type	77°
	Software function	Video, Picture, Beauty, Bokeh, Mono, Water Mark, Mirror, Fill light
	Rear Camera 48MP+8	MP+2MP+30W
	Sensor	Samsung S5KGM1ST03-FGX9 48MP
Rear	Sensing area	1/2.25inch
Camera	Pixel area	6000*8000
	Aperture	F/1.8±5%
	Sensor type	79±3°

### DORLAND

	1	www.dorland-tech.com
	PDAF	Support
	Flash led	Support
	Software function	Panorama, Video, Picture, Beauty, Bokeh, Pro, Mono, HDR, Water Mark
Macro	Sensor	GC02M2 2MP
	Sensing area	1/5inch
	Pixel area	1616*1224
	Aperture	F/ 2.8± 5%
	Sensor type	75°
	Software function	Video, Picture
	Sensor	Samsung,s5k4h7 8MP
	Sensing area	1/4inch
Wide-ang	Pixel area	2448*3264
le	Aperture	2.2±5%
	Sensor type	118.8°
	PDAF	AF
	Size & technology	6.39" IPS
	Screen color	16.7M
	Туре	LCD
<b>5</b> : 1	Resolution	720*1560 HD+
Display	Pixel density	270ppi
	Aspect Ratio	19:09
	Brightness	430cd/m2 (MIN)
	Screen contrast	1000/1
	navigation	Support, Beidou, Galileo, Glonass, GPS
	WIFI	Support, 2.4G/5G ( 802.11ac/a/b/g/n )
Transmis	Bluetooth	Support, BT5.2
sion	FM	Support / plug in headphones support external playback
function	OTG	Support
	NFC	Support, Google pay
	G-sensor	Support, triaxial
Sensor	Other sensors	Support, Proximity sensor, Ambient light senor, Compass (magnetic),
		Geomagnetism, Gyroscope
		ICNF723A2L
		Coating surface material
		No stainless steel metal ring
Unlock	Side fingerprint	0.19s response speed
method	identification	360° identification angle
		Capacitance touch sensor
		508DPI scanning resolution
Hardware	Wireless charge	Support
features	Rapid Charge	Support, maximum charge 11V/3A
	Iapia Oriargo	- append maximum energy 11 trong

# DORLAND

	1	www.dorland-tech.com
	Sound Amplifier	Intelligent power amplifier, FS1894SU
Touch panel	Panel technology	Double layer multipoint
	IC	FT8615-AB
	Sensor technology	Capacitive touch screen
	Material	Panda tempered glass
	Fitting method with Display	Full paste
<b>D.</b>	Power button	Support
Physical	Volume button	Support
buttons	Custom key function	Support
\" I	Home button	Support
Virtual	Menu button	Support
buttons	Return button	Support
Electric	Speaker	1813 box single box horn rated 1.0W, maximum 1.2W
	Motor	827
acoustic	Receiver	1008 Shrapnel type
devices	Mic	Silicon wheat
Deat	Headphone port	N/A
Port	Charger interface	Туре-с
Dottoni	Capacity	8500mAh
Battery	Voltage	4.4V
Software function		Description
	System navigation	Gesture navigation, 3-button navigation
		Gesture support is subject to the actual situation, and this function is
	Smart gesture	turned off by default
	Smart gesture  Communication	
System		turned off by default
System function	Communication	turned off by default  Support, Flip mute and intelligent answer are turned off by default, and
-	Communication somatosensory  System	turned off by default  Support, Flip mute and intelligent answer are turned off by default, and wake up when picking up the device is turned on by default  Support, Three finger screen capture, three finger access to the camera, two finger volume adjustment, alarm clock flip pause. This function is off
-	Communication somatosensory  System somatosensory	turned off by default  Support, Flip mute and intelligent answer are turned off by default, and wake up when picking up the device is turned on by default  Support, Three finger screen capture, three finger access to the camera, two finger volume adjustment, alarm clock flip pause. This function is off by default
-	Communication somatosensory  System somatosensory  FOTA upgrade OTA	turned off by default  Support, Flip mute and intelligent answer are turned off by default, and wake up when picking up the device is turned on by default  Support, Three finger screen capture, three finger access to the camera, two finger volume adjustment, alarm clock flip pause. This function is off by default  Support  English, Simplified Chinese, Traditional Chinese, etc. (It has updated 48)
-	Communication somatosensory  System somatosensory  FOTA upgrade OTA  Supported languages	turned off by default  Support, Flip mute and intelligent answer are turned off by default, and wake up when picking up the device is turned on by default  Support, Three finger screen capture, three finger access to the camera, two finger volume adjustment, alarm clock flip pause. This function is off by default  Support  English, Simplified Chinese, Traditional Chinese, etc. (It has updated 48 languages)  Support AVI, MP4,, MKV, MOV, ASF, FLV and other video formats, up to
function	Communication somatosensory  System somatosensory  FOTA upgrade OTA  Supported languages  Video playback	turned off by default  Support, Flip mute and intelligent answer are turned off by default, and wake up when picking up the device is turned on by default  Support, Three finger screen capture, three finger access to the camera, two finger volume adjustment, alarm clock flip pause. This function is off by default  Support  English, Simplified Chinese, Traditional Chinese, etc. (It has updated 48 languages)  Support AVI, MP4,, MKV, MOV, ASF, FLV and other video formats, up to 1080P/30fps
function  Entertain ment	Communication somatosensory  System somatosensory  FOTA upgrade OTA  Supported languages  Video playback  Video produce	turned off by default  Support, Flip mute and intelligent answer are turned off by default, and wake up when picking up the device is turned on by default  Support, Three finger screen capture, three finger access to the camera, two finger volume adjustment, alarm clock flip pause. This function is off by default  Support  English, Simplified Chinese, Traditional Chinese, etc. (It has updated 48 languages)  Support AVI, MP4,, MKV, MOV, ASF, FLV and other video formats, up to 1080P/30fps  Highest support 1080P@30fps video shooting  Support MP3, AAC, AMRAnd other video formats / supports lossless

Tel: +86-10-62198496 Fax: +86 010 62985217 www.dorland-tech.com tian@dorland.com.cn

## DORLAND

#### www.dorland-tech.com

		www.dorland-tech.com
Other software	Market	Support
	Share	Support
	Software Toolbox	Compass, Gradienter, pedometer, Pic Hanging, HeightMeasure,
		Magnifier, Alarm bell, Plumb Bob, Protractor, SoundMeter
Accessories		Description
Package Contents	Cellphone	x1
	Type-C USB	x1, 2A
	Charger	x1, 12V/2A
	Explosion-proof film	x1
	Explosion-proof film	x1
	Card Slot Opener	x1
	Sling	x1
	Packing box	x1
	manual	x1
	Frosted PE bag	x1
	warranty card	x1



www.dorland-tech.com



Certificate No.:

**CCRI 21.2841** 

Company:

Beijing Dorland System Control Tech Co., Ltd.

Address:

Room 807, Yingu Plaza, North 4th Ring West Road, Haidian District,

Beijing 100080, P.R. China

Name of Product:

**Industrial Intrinsically Safe 5G Smartphone** 

Type of Product:

Extreme\_5G

Marking:

Ex ib IIC T4 Gb / Ex ibD 21 T130°C

Technical Documents:

Q/DLM 003-2021

Drawing No.:

Extreme\_5G BZ01

Note(s):

1. The rated voltage is DC 3.8V, Powered by a dual-protected polymer lithium-ion battery, Model: Ex battery 053, Nominal capacity: 8500mAh; 2.Ambient temperature range:-20°C\u2265Ta\u2264+60°C;IP code:IP68@1.5m, 30min;

3. Do not charge in hazardous locations;

By verifying the drawings and technical documents and checking samples, the product complies with the following standards currently valid in P.R.China:

GB 3836.1-2010, GB 3836.4-2010, GB/T 4208-2017, GB 12476.1-2013, GB 12476.4-2010

Date of Issue:

05.01.2022

Valid till:

04.01.2027

Authorize:

China Coal Research Institute Testing Center

(The test center of the national safety production of mining equipment and mining oil in Beijing)

Note: This certificate is only valid for the products that are in accord with samples tested and verified. Center Add: No.5 Qingniangou Road, Hepingli, Beijing, 100013

The query url of Explosion-proof Certificate: http://www.ccritc.com.cn/Home

Tel/fax: 010-89268018