

Dorland Industrial Intrinsically Safe PDA Ex PDA 7100/7200

Newly released by Beijing Dorland System Control Technology Co. Ltd., the industrial intrinsically safe smart handheld terminal ExPDA 7100/7200, adopts advanced technology, designed with intrinsically safe circuit, and with rugged and solid body. This model carries OS Android11.0 and high-performance quad-core CPU, equipped with built-in RFID, barcode scanning, NFC, iris identification, HD cameras, GPS and other modules and functions suitable for outdoor construction and pipeline inspection. It can cooperate with OA office system, checking positioning system and data acquisition system and other applications, especially suitably used in dangerous environment such as petroleum, chemical, pharmaceutical, oil depot, tank farm and other hazardous sites with combustible and explosive gas. This product shall facilitate users' timely communication with the production management.

Protection Grade: IP65

Explosive-proof Grade: Ex ib IIC T4 Gb/Ex ib D21 T130°C

Explosive-proof Certificate No.: CCRI 19.2166

OS: Android 11.0

Screen: 5.2", IPS FHD 1920x1080

RAM+ROM: 3GB+32GB / 4GB+64GB

(6GB+64GB / 6GB+128GB Customization)

Storage Card: SD card up to 128GB

CPU: Cortex-A53 2.5 / 2.3 GHz 8-core

Cameras: Rear 13.0 MP AF, flash; front 5.0 MP

Frequency:

2G GSM850/GSM900/DCS1800/PCS1900

3G WCDMA: B1/B2/B4/B5/B8 CDMA2000 EVDO: BC0

TD-SCDMA: A/F

4G B1/B2/B3/B4/B5/B7/B8/B12/B17/B20/B28A/

B28B/B34/B38/B39/B40/B41

Dimensions: 164.2*78.8*17.5mm/164.2mm x 80.0mm x 24.3mm

Battery: 5000mAh/8000mAh

Standby Time: >350 hrs

Working Time: >12 hrs

NFC: yes

Barcode Collection (optional)

1D Module: Zebra SE965 / Honeywell N4313

Pro 1D barcode type:

UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.



RFID UHF (optional)	
Operating frequency (860-960 MHz, customized frequency band as required)	
Chinese frequency	920-925 MHz
Us frequency	902-928 MHz
European frequency	865-868 MHz (ETSI EN 302 208)
Other frequencies	Other multinational frequency standards (customizable)
engine	Cm2000-1, based on Impinj Indy R2000;
Cm710-1, based on Impinj e710 chip (forthcoming)	
Protocol standard	EPC C1 GEN2 / ISO18000-6C
Antenna parameters	Linearly polarized antenna (1.8 DBI) / circularly polarized antenna (4dbi)
power	1 W (30 DBM, supporting + 5 DBM to + 30 DBM adjustment)
Optional 2 w (33 DBM for Latin America, etc.)	
Card reading distance	Up to 15m (circular polarization, outdoor open environment, Impinj mr6 label);
Up to 7m (linear polarization, outdoor open environment)	
Group read rate	Up to 900 tags / S (circular polarization)
*The card reading distance and group reading rate are related to the actual environment	
NFC (optional)	
Operating frequency	13.56 MHz
Protocol standard	ISO14443a / B, ISO15693, nfc-1p1, nfc-1p2, etc
Label standard	M1 card (S50, S70), CPU card, NFC tag, etc
Read write distance	2-4 cm
*Four core optional, eight core standard	
Bar code acquisition (optional)	
One dimensional scanning engine	Zebra: SE965; Honeywell: N4313
Support one-dimensional barcode type	UPC / EAN, CODE128, CODE39, CODE93, CODE11, INTERLEAVED 2 OF 5, DISCRETE 2 OF 5, CHINESE 2 OF 5, CODEBAR, MSI, RSS, etc
2D scanning engine	Zebra: SE4710 / SE4750 / SE4750MR; Honeywell: N6603
Support 2D barcode type	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal codes: US Postnet, US Planet, UK postal, Australian postal, Japan postal, Dutch postal (KIX), etc

Beijing Dorland
System Control
Technology Co., Ltd.

Room1107, Tower B, Tsinghua
Tongfang Technology Square,
No.1 Wangzhuang Road,
Haidian District, Beijing, P.R.China

Tel: +86-10-62198496
Fax: +86 010 62985217

www.dorland-tech.com
tian@dorland.com.cn

DORLAND
www.dorland-tech.com



ADD: Room1107, Tower B, Tsinghua Tongfang Technology Square, No.1 Wangzhuang Road, Haidian District,
Beijing, P.R.China.

 170021131268	 CNAS L0738	中国认可 检测 TESTING CNAS L0738
 CCRIC	CONFORMITY CERTIFICATE OF EXPLOSION-PROOF	
Certificate No.:		CCRI 19.2166
Company:	Beijing Dorland System Control Tech Co.,Ltd.	
Address:	Room 11B5,Huajie Plaza Dazhongsi Street,Haidian District, Beijing 100098,P.R.China	
Name of Product:	Industrial Intrinsically Safe Handheld Terminal	
Type of Product:	Ex PDA 7100/7200	
Marking:	Ex ib II C T4 Gb / Ex ibD 21 T130℃	
Technical Documents:	Q/DLM 004-2019	
Drawing No.:	Ex PDA 7100/7200 BZ01	
Note(s):	1. Power supply by dual protection rechargeable lithiumion battery with rated voltage 3.7VDC, battery type:Ex Battery 025, 5000mAh; 2. IP code:IP65.	
By verifying the drawings and technical documents and checking samples,the product complies with the following standards currently valid in P.R.China: GB 3836.1-2010, GB 3836.4-2010, GB 12476.1-2013, GB 12476.4-2010, GB/T 4208-2017		
Date of Issue:	6.26.2019	
Valid till:	6.25.2024	
Authorize:	 	
China Coal Research Institute Testing Center		
(The test center of the national safety production of mining equipment and mining oil in Beijing)		
Note: This certificate is only valid for the products that are in accord with samples tested and verified. Center Add: No.5 Qingniangou Road,Hepingli,Beijing,100013 Tel/fax: 010-89268018 The query url of Explosion-proof Certificate: http://www.ccrict.com.cn/Home		